



ML20-500 Series

High Pressure Washers

500 Bar @ 15 LPM

Comes with:

- 4-core oil resistance electric cable
- High pressure hose with SS Fittings
- High pressure gun with lance

Highlights:

- Europe Components
- Triplex Ceramic Plungers
- Low water inlet pressure protection
- Unloader valve with pressure release
- Thermal Protection Valve

CAPABILITIES

- ☒ **GENERAL WASHING**
- ☒ **STUBBORN STAINS**
- ☒ **SPOT DE-RUSTING**
- ☒ **SPOT PAINT-REMOVAL**



High Pressure Clean-
ing companies



Building Sites
and boat yards



Iron and Steelworks
and engineering firms



F&B



Oil & Gas



2440D-03V32-TC
3/16" - 26,100 psi
Ultra High Pressure Flex Lance Hose

Equivalent to Hose Type 5/4

Water Blast: Heat Exchanger Tube
 Cleaning

Hydraulics: Hydraulic Jacks, Hydraulic
 Tools, Bolt Tensioning



ProLance
 Shortest & Most
 Compact Fitting!



BOP Hose

Blow out Prevention
 Standard Colour:

x3 - Green

x2 - Blue

x6 - Yellow

2390N-04V1x; 1/4" - 7,100 psi Hose
2390N-06V1x; 3/8" - 6,450 psi Hose
2390N-08V1x; 1/2" - 6,017 psi Hose
2380N-16V1x; 1" - 5,510 psi Hose

Design Factor
 4:1

Temperature range
 -40°F to +212°F (-40°C to +100°C)
 at a 4:1 design factor;
 Max of +158°F (+70°C) for water,
 glycol or methanol-based fluids



PFX30-05x
5/16" - 43,645 PSI
Ultra High Pressure Waterblast Hose

More robust than common 6
 layer constructions

Water Blast: Main Hose




2740D-03V3x
3/16" - 40,600
Ultra High Pressure Waterblast Hose

Water Blast: Gun Hose

HAMMELMANN

HDP Series, a professional heavy-duty High-Pressure water blaster with a high-performance UHP pump, carbide and ceramic plungers with inter-cooling system



HDP 72 Series

Power consumption	70 kW
Pump Input RPM	1500/1800
Weight (Kg)	1150
Dimension (mm)	1502 X 1105 X 720

MAWP: up to 1130 Bar/ 16,380 PSI

Flow rate: up to 31 l/min.

Diesel Model

Suitable for Heat Exchanger Cleaning

HDP 204 Series

Power consumption	200 kW
Pump Input RPM	1800/2150
Weight (Kg)	3200
Dimension (mm)	2560 X 1540 X 2050

MAWP: up to 2700 bar/ 39,160 PSI

Flow rate: up to 41 l/min.

Diesel Model

Suitable for Rust removal with Spiderjet
Magnetic Crawler





Compressors

up to 410 CFM

XAHS 400 PACE

Working pressure: 7 Bar / 100 PSI

Free Air Delivery: 410 CFM

Engine: Cummins

Compressors



up to 850 CFM

XAHS 850 PACE

Working pressure: 5-12 Bar/ 72-175 PSI

Free Air Delivery: 848 - 679 CFM

Engine: Cummins



7 bar: Handheld tools



8.6 to 10 bar:
Abrasive blasting




7 to 12 bar:
Shotcrete applications



12 to 14 bar:
Cable blowing and drilling

SALES@OLSOMENS.COM

05/10 1000 bar /



 SINGLE 500 bar / 7250 psi
 ROTOR 1000 bar / 14500 psi
CE 2016/425/PPE


 SINGLE 1000 bar / 1450 psi
 ROTOR 2800 bar / 40000 psi
CE 2016/425/PPE

 SINGLE 2000 bar / 30000 psi

 ROTOR 3000 bar / 43500 psi


 CE 2016/425/PPE

Protection level	Pressure bar (psi)	Flow L/MIN (gpm)	Nozzles		Speed RPM	Distance mm(in.)	Linear Speed m/s (in./sec.)	Result
			N	Dia.mm(in.)				
05/10	500(7250)	17.7(4.7)	1	1.3(.050)	---	75(3)	0.7(27.6)	No Penetration
05/10	1000(15000)	17.9(4.7)	4	0.55(.021)	3000	75(3)	0.7(27.6)	No Penetration
10/28	1000(15000)	16.1(4.3)	1	0.9(.035)	---	75(3)	0.7(27.6)	No Penetration
10/28	2800(40000)	15.6(4.1)	4	0.4(.016)	3000	75(3)	0.7(27.6)	No Penetration
20/30	2000(30000)	13.4(3.5)	1	0.8(.031)	---	75(3)	0.7(27.6)	No Penetration
20/30	3000(43500)	13.6(3.5)	4	0.35(.014)	3000	75(3)	0.7(27.6)	No Penetration



ACCESSORIES

Aqua Safe Hose Shroud is a safety sleeve that securely attaches to the high-pressure hose connection on a spray gun, providing the operator with extra protection against potential hose leaks.
Spec: OAL: 150 cm, Diameter: 60mm, Protection: 2800bar



Banshee

Tube Cleaning - Heat Exchanger Cleaning

Available in Size:

9.5mm, 13mm, 15mm, 18mm

Available in Pressure:

15k psi / 1000 bar to 40k psi / 2800 bar



Sapphire Hydro-blast Nozzles Available too!

Type M Nozzles, OS4, OS6, OS7
Equivalent

Heat Treated and Manufactured with
17-4 SS

Orifice sizes are available from .003"
to .040" (.076mm to 1 mm)

Rated up to 60,000 PSI / 4138 bar



Barracuda Surface Prep

44,000 PSI / 3000 bar

Length: 7.8 in. / 8.9 in.

Weight: 2.9 lb / 3.2 lb

Diameter: 1.8 / 2.5 in.

Part #: BC-HP



Gopher Pipe Cleaning

40,000 / 2800 bar

Length: 7.8 in. / 19.81 cm

Weight: 3.31 lb / 1.5 kg

Pressure Range: 22-40k psi
1500-2800 bar

Part #: GO-H9-C-UNP-PKG